





CSS – OD / Commercial Storage Solution for Installations with BUI100










Quick Installation Guide

for Europe, APAC
and South Africa

Legend

-  **WARNING!** This symbol denotes a hazard. It calls attention to a procedure that if not correctly performed or adhered to could result in injury or loss of life. Do not proceed beyond a warning note until the indicated conditions are fully understood and met.
-  **CAUTION!** Denotes a hazard. It calls attention to a procedure that, if not correctly performed or adhered to, could result in damage or destruction of the product. Do not proceed beyond a caution sign until the indicated conditions are fully understood and met.

Safety Instructions

-  **WARNING: RISK OF ELECTRIC SHOCK**
DO NOT touch the wires, contacts, terminals, or any conductors connected to the grid circuit inside the equipment.
Failure to follow safety instructions could result in severe injury or death from electric shock.
-  **WARNING: LETHAL HIGH VOLTAGES exist inside the product.**
 - Note and abide by all warning signs on the product.
 - Observe the safety precautions listed in this manual and other related documents.
-  **WARNING: Damaged Equipment Hazards**
 - Damaged equipment or system failure may cause electric shock or fire!
 - Perform an initial visual inspection of the equipment for damage or other hazards before operation.
 - Check whether other external devices or circuit connections are secure.
 - Confirm that this equipment is in a safe state before operating it.
-  **WARNING:** This equipment must be installed by **licensed electrician** and qualified personnel only. The installation and wiring of this equipment must comply with all applicable national, state/provincial, local electrical codes and standards. Attempting installation by unqualified individuals could result in unsafe operation, code violations, personal injury/loss of life, or damage to the equipment.
-  **WARNING: Battery Protection**
DC HIGH VOLTAGE! ELECTRIC SHOCK HAZARD!
The battery in the system generates a high voltage when connected. Accidental contact can result in electric shock or life-threatening injuries.
-  **WARNING: Ground Fault Protection**
 - When a ground fault occurs in the integrated PCS, there may be fatal high voltage in parts that are not originally charged. DANGEROUS IF ACCIDENTALLY TOUCHED!
 - Before operation, ensure there is no ground fault in the system, and take relevant protective measures.
-  **WARNING: Live Line Measurement**
 - There are high voltages in the equipment in the integrated PCS, and accidental touch may cause fatal electric shock hazards.
 - During live measurement, take appropriate protection, such as wearing insulating gloves.
 - There must be an accompanying person to ensure personal safety.
-  **WARNING: Improper parameter settings**
 - Improper parameter settings may affect the normal function realization of internal devices.
 - Only authorized professionals can set the parameters.
-  **WARNING: Regulatory Compliance**
The installation and various operations of the integrated PCS must comply with the relevant standards and regulations of the country/region where the project is located

Work Clothes



Safety Robber Shoes



Helmet



Robber Gloves



Safety Clothing



Goggles

 **WARNING!** Use **only** insulated and protected tools.

Battery Cabinet 102.4 kWh & Battery Inverter 50 kW



Torque wrench with 7mm, 10mm, 17mm, 18mm, 19mm sockets



Wire Cutter



Crimping tool



Phillips screwdriver $\varnothing 6$ mm, L= 230 mm



Heat gun



Multimeter



Cable Stripper



Wire Stripper



Drill



Box Cutter



Pipe Cutter

Commercial Backup Interface 100 kW



Ladder



Hammer



Flat Head Screwdriver



Flat Head Screwdriver for Terminal Block Screws



Torque wrench with M4, M6, M10, M12 sockets





Adjustable Wrench




Open-end torque wrench

General Description of Battery Cabinet & Battery Inverter



1. Battery Cabinet HVAC
2. Battery Inverter 50 kW
3. Emergency Power Off (EPO) switch
4. CSS Local Interface
5. Wiring Duct
6. Photoelectric Smoke Detector
7. Aerosol Fire Extinguisher 1
8. Aerosol Fire Extinguisher 2
9. Cluster 1 (10 EMs + CMU1)
10. Cluster 2 (10 EMs + CMU2)
11. Cluster Management Unit 1
12. Cluster Management Unit 2
13. AC Interface Box
14. Battery Cabinet Management Unit
15. Energy Module (x20)
16. Energy Module Management Unit

General Description of Commercial Backup Interface (BUI100)




1. Diesel Generator Energy Meter
2. Grid Energy Meter
3. SolarEdge ONE Controller
4. CSS Local Interface
5. Emergency Power Off (EPO) switch
6. Technical Documentation Folder
7. X04: Battery Inverter comm. interface
8. XT3: Terminal Board
9. BUI Ethernet I/O
10. QBP.GRID: Grid Bypass MCCB
11. Mechanical Interlock between QLOAD, QBPGRID and QBPDG
12. QLOAD: Combined PV & LOAD input MCCB
13. QBP.DG: Diesel Generator Bypass MCCB
14. QPCS2: Battery inverter 2 Input MCCB
15. QPCS1: Battery inverter 1 Input MCCB
16. F13: Surge Protection Device Fuse
17. QGRID: Grid input MCCB
18. QDG.APS and QGRID.APS:
230VAC auxiliary power supply MCBs from DG & GRID
19. QDG: Diesel Generator Input MCCB
20. QAC1 & QAC2: A/C (HVAC) supply MCBs to PCS1 & PCS2
21. F10: FAN1 & FAN2 of power transformer compartment fuse
F11: Control power fuse of DG contactor K2
F12: Control power fuse of GRID contactor K1
22. Replaceable AC SPD (per phase)
23. F7: 500V DC auxiliary power supply (from PCS) fuse
F8: 230VAC auxiliary power supply from DG fuse
F9: 230VAC auxiliary power supply from GRID fuse
24. QDC.APS: 500V DC auxiliary power supply (from PCS) MCB
25. F1: Battery Inverter voltage sampling protection fuse
F2: Neutral voltage sampling fuse
F3: Inverter voltage sampling protection fuse
F4: GRID/DG voltage sampling protection fuse
F5: DG voltage sampling & DG meter protection fuse
26. XT1: AC Auxiliary terminal block
27. XT2: DC Auxiliary terminal block
28. PE wires connection bus
29. DIN rail for optional Isometer & Coupling Device
30. Air filter

**Battery Cabinet
102.4 kWh**



1433 KG

**Battery Inverter
50 kW**



73 KG

**Battery Inverter 50 kW
Battery Cabinet 102.4 kWh**
*Assembled Dimensions



1506 KG


**Commercial Backup
Interface 100 kW**



960 KG

Default Layout & Clearance Distances (Top View)

All dimensions are in [mm]



Battery Cabinet + Battery Inverter	
Direction	Distance [mm]
Front	1200
Rear	400
Right	1000
Left	600


Standalone Battery Cabinet 102.4 kWh	
Direction	Distance [mm]
Front	1200
Rear	400
Right	600
Left	600

Commercial Backup Interface 100 kW	
Direction	Distance [mm]
Front	1200
Rear	1200
Right	600
Left	1000

NOTE!
 Installers are hereby notified that local codes and regulations could extend the required clearances beyond what is specified in this manual. Before proceeding with installation, consult with relevant authorities to ensure compliance with local regulations concerning clearance distances.



Option 2: BUI100 in the middle




Option 3: Batteries back-to-back




Option 4: Row Positioning


CAUTIONS and Requirements of Installation Environment

- When the equipment is running, do not cover the vents or heat dissipation system to prevent fire due to high temperature.
- The equipment should be installed in an area away from liquids; it is forbidden to install it under water pipes, air outlets and other places that are prone to condensation, or under places that are prone to water leakage, such as air-conditioning outlets, vents, and outlet windows in the machine room, to prevent liquids from entering the inside of the equipment and causing malfunction or short circuit.
- If any liquid enters the equipment, please turn off the power immediately and notify the administrator.
- Do not place the equipment in an environment with flammable or explosive gas or smoke, and do not perform any operations in such environment.
- The equipment should be installed away from desert or sandy environment.


CAUTION! For indoor installations ventilated room is required 

CAUTION! CSS – OD solution must be installed: >2km from the sea when installed in outdoor location or >1km when installed in indoor locations. 

CAUTION! When Installed in indoor locations consider heat dissipation values of all installed devices when choosing appropriate room / space for their installation

NOTE! Battery Cabinet & Battery Inverter max noise is >65 dBA, 1 meter distance 

Battery Cabinet	
Max Power	Heat Dissipated
50KW	0.87 KW·h 2970 BTU
Battery Inverter	
Max Power	Heat Dissipated
50KW	1.5K W·h 5118 BTU
BUI100	
Max Power	Heat Dissipated
100KW	3.35 KW·h 11430 BTU




- ***Three Phase AC Cable , Multi stranded class 5 or 6, 120 mm², 150 kW
- Three Phase AC Cable, Multi stranded class 5 or 6, 35 mm², 50 kW
- Single Phase Auxiliary AC Cable
- - - DC+ & DC- Power cables (x2)
- DC Auxiliary
- Modbus TCP Comm. Cable (LAN)
- CAN Comm. Cable (LAN)
- ***Meter RS-485 Comm. Cable (Not Supplied)
- - - - - ***Dry contacts Control Cable (Not Supplied)


***Not Supplied

Supported Site Configurations


Configuration 1 - Fully Backed-up site (Pages 28-29)




Configuration 2 - Partially Backed-up site – (Pages 31 – 32)




Configuration 3 - Fully Backed-up site with 3rd party ATS Gear (Page 34)




Configuration 4 - Partially Backed-up site with 3rd party ATS Gear (Pages 35)



Transporting Battery Cabinet with the wooden box





Transporting Battery Cabinet Standalone




Forklift Requirements

WARNING! Forklift must be able to lift At least 5 tons carrying capacity




Transporting BUI100 inside wooden box



Floor Pallet


Transporting BUI100 Standalone




IMPORTANT!
Use wood block

Forklift Requirements

WARNING! Forklift must be able to lift At least 5 tons carrying capacity






Unpacking Commercial Backup Interface 100






NOTE! Disassembly of wooden box must start from the top side

NOTE: Use flat head screwdriver to unfold the connecting buckles



NOTE: Forklift Slot Covers (x2) are supplied inside the package. Keep the Slot Covers for closing BUI bottom openings once positioned in the final location.





IMPORTANT!



1. Open Steel Frame must be provided by the customer.
2. General Dimensions & Requirements of the steel frame are provided in Appendix A.
3. Customer's civil engineer shall review and approve the customers provided structure (open steel frame).

Unpacking Battery Cabinets



NOTE! Disassembly of wooden box must start from the top side

NOTE: Use flat head screwdriver to unfold the connecting buckles



NOTE: Scrap the **front** and **rear** brackets



Remove M12 nuts using 19 mm socket (x8)



NOTE: For the side brackets, remove only screws connecting to pallet. (x4)


1

NOTE! These expansion bolts & washers are **not supplied**. Torque is dependent on mounting surface. For concrete: 60Nm



X4 (X2 on each side)

NOTE: Bolts and washers are **not supplied**



NOTE!
For steel frame production guidelines, see Appendix A.


IMPORTANT!

1. Open Steel Frame must be provided by the customer.
2. General Dimensions & Requirements of the steel frame are provided in Appendix A.
3. Customer's civil engineer shall review and approve the customer's provided structure (open steel frame).


Mounting Battery Cabinet Directly on Concrete Pad

NOTE! Concrete pad guidelines are in Appendix A

Option 1: Concrete Pad with pre-integrated studs



Option 2: Concrete Pad & Drilling occurs on site



All dimensions are in [mm]

Battery Cabinet Package Contents (Inside Accessories Box)

Battery Cabinet (Cluster 1)
to Battery Inverter DC Cables (3m) (A)




BAT1

Battery Cabinet (Cluster 2)
to Battery Inverter DC Cables (3.5m) (B)



BAT2



△ PAY ATTENTION!
All Cables are marked
with a designation label

Battery Cabinet to
Battery Inverter
CAN cables (3.5m) (C)



PCS-COM

PE cable (0.7m) (E)



Battery Cabinet to Battery
Inverter RS485 cable (3.5m)



**△ THIS PROVIDED CABLE
SHOULD NOT BE USED**


Battery Cabinet to BUI100
AC Auxiliary Cable (10m) (D)




Battery Cabinet to BUI100
Modbus TCP Cable (10m) (F)



Battery Cabinet
Wiring Duct (G)



Forklift Slots Covers (x4) (Y)
(Outside Accessories Box)



Battery Cabinet Package Contents (Inside Battery Cabinet)

Fire Clay (x2) (H)



Corrugated Plastic
Tube Ø 34.5 mm (I)





Corrugated Plastic
Tube Ø 21 mm (J)




Battery Inverter Package Contents

Battery Inverter Mounting Bracket (K)




Battery Inverter

Battery inverter to BUI100 Parameters Communication Cable (10m) (L)




Battery Inverter to BUI100 DC Auxiliary Cable (10m) (M)



<p>DC-Bus Connector (N)</p>	<p>Communication Cable Connector (O)</p>	<p>Right-angled Phillips screwdriver (P)</p>
<p>Bracket Mounting Screws (x4) (Q) 17mm x 30</p>	<p>Bracket Lock Screws (x2) (R) 10mm x 16</p>	<p>M6 Lugs (x5) (S)</p>
<p>Cables Shrinks (x5) (T)</p>		

Cabling Extension Kit box*

Cluster to Cluster Paralleling
DC+ Cables (x2) (5m) (U)



BAT1

BAT2

Cluster to Cluster Paralleling
DC- Cables (x2) (5m) (V)



BAT1

BAT2


Battery Cabinet to Battery Cabinet
AC Auxiliary Cable (5m) (W)



Battery Cabinet to BUI100
Modbus TCP Cable (5m) (X)




PAY ATTENTION!
All Cables are marked
with a designation label





*This kit is ordered separately for 2:1 installations

Metering Kit*




CSS Meter (Y)

Current Transformers
for CSS Meter (x3) (Z)

*This kit is ordered separately for configuration 2 & 4: Site with partial backup


Mounting the Battery Inverter onto Battery Cabinet





Get parts from:
Battery Cabinet Package


A, B, C, E, I, J



WARNING! HAZARD OF ELECTRIC SHOCK. DISCONNECT POWER BEFORE INSTALLATION OR SERVICE – TURN SWITCHES TO OFF





Battery Inverter



NOTE! Cut the corrugated tubes to the required length.


3

Detailed wiring is provided on the next 2 pages



I
E

Wiring Single Battery Cabinet to Battery Inverter



Wiring two Battery Cabinets to Battery Inverter




Get parts from: Cabling Extension Kit Package*
U(X2), V(X2), W, X



Get parts from: Battery Cabinet Package
A, B, C, (+I, J)




WARNING! HAZARD OF ELECTRIC SHOCK. DISCONNECT POWER BEFORE INSTALLATION OR SERVICE – TURN SWITCHES TO OFF




PAY ATTENTION!
Do Not connect this cable to an Ethernet switch. Connecting this cable to a switch may damage the switch.

*This kit is ordered separately for 2:1 installations





- IMPORTANT NOTE!**
1. Communication cables and power wires **must** be laid separately (DC and AC loops).
 2. The distance between different cables must be greater than 30mm. In cases when control cables crosses power cables, validate that the angle between the two cables is kept at 90°.
 3. The recommended minimum distance between parallel shielded data cables and power cables is shown below:

Parallel length (m)	Min space distance (m)
200	0.3
300	0.5
500	1.2




Battery Inverter



- Pin 1. RS485-A - Black
- Pin 2. RS485-B - Brown
- Pin 3. CAN-H - Red
- Pin 4. CAN-L - Orange
- Pin 5. Zero Cross - Yellow
- Pin 6. EPO - Green
- Pin 7. Carrier - blue
- Pin 8. GND - Purple


NOTE: Make sure that gland points to the left & graphics faces front

 For Battery Inverter side, lugs & shrinks are provided inside the Battery Inverter package.
S (x5), T(x5)

NOTE: Cable properties: (Not provided)


- Multi stranded class 5 or 6 flexible conductors.
- Up to 35 mm² cross section wires cable.
- Cable maximum power is 50 kW.
- Crimp M6 lugs (provided with the Battery Inverter).

BUI100





From Battery Inverter 1
From Battery Inverter 2


IMPORTANT! To ensure proper operation, install ferrite bead

 **Get parts from:**
Battery Inverter Package
L, M, N, O

NOTE: Lugs are not provided. Use M6/up to 35 mm² compatible lugs




NOTE: To access the X04 board, remove first the protective cover



Wiring Battery Cabinets to BUI100


IMPORTANT! Each Battery Cabinet must be connected to the BUI100 in the provided method, regardless of 1:1 or 2:1 use case on site







Wiring Duct Lid Closing & External Cables Wiring Method

IMPORTANT! Use fire clay to block the cable gaps and seal un-routed wiring holes.


Fire Clay (x2) (H)



Get parts from: Battery Cabinet Package (H, G [Duct Cover])




Connecting BUI100 to Grid, Load + PV Inputs





BUI100

NOTE! All shown cables are not provided




Connecting BUI100 to CSS External Meter






Connecting BUI100 with external Automatic Transfer Switch & Critical & Non-Critical Loads




Connecting SolarEdge ONE Controller to Local Gateway

BUI100




*CAT5/6 three-wire shielded twisted pair (0.2- 1 mm²)



Connecting Grid / Diesel Generator / PV to BUI100 EPO (Optional)

BUI100



IMPORTANT! When the BUI trips, all external power sources trip simultaneously. If connected to EPO Relay 1


Grid



Load + PV



Diesel Generator




EPO Relay 1

N.O Contacts, load (resistive) 5A
220VAC/24VDC

Follow the numbered steps to power up the system

Step 2 – Initiate Battery Inverters DC Switches
 Step 3 – Initiate Battery Cabinets


Step 1 – Power Up BUI100
 (On-Grid Operation)








Appendix A

Electrical Component Requirements & Construction Details



1. Rated short-circuit breaking capacity current $I_{cu} \leq$ GRID maximum short circuit current.
2. Instantaneous protection against short-circuit should not exceed minimum phase to earth short circuit current provided by the power supply (consider the low level of short circuit current supplied by DG and PV).
3. Instantaneous short circuit protection of the GRID and DG feeders must ensure protection of the PV+LOAD panel (fed from the BUI) from minimum short circuit current.
This protection should be considered:
 - A. When fed from the GRIG, QBPGRID is closed.
 - B. When fed from DG QBPDG is closed.
4. Customer circuit breakers supplying BUI100 from GRID, DG and PV should be equipped with trip coil to trip power sources in case of Emergency Stop signal from the BUI.
Trip signal from the BUI (C/O) contact is 400mS.
5. No other devices shall be connected to this Circuit Breaker. It shall serve only the dedicated power source it is connected to in series.

All dimensions are in [mm]




11	footboard	1
10	U-steel C	4
9	U-steel	2
8	U-steel	2
7	Unequal Angle steel G	2
6	Unequal Angle steel F	2
5	Unequal Angle steel E	4
4	Unequal Angle steel	4
3	Unequal Angle steel	1
2	Unequal Angle steel	2
1	Unequal Angle steel	2
No	A Part Name	qty




Technical Requirements:

1. Solid welding, no virtual welding.
2. After welding, except for welding slag, the outer surface of the parts is polished and smooth.
3. Spray protection according to the requirements of the drawing, all stud end faces and threads need spray protection.
4. No dimensioned tolerance according to GB/T 1804-M processing.
5. The unmarked position tolerance shall be executed in GB/T 1184-K class.
6. With* number is an important size, need to focus on inspection.
7. For other dimensions not specified, refer to the 2D/3D drawing.

U-steel and Angle steel are both Q235A
Surface: hot dipping galvanized




Battery Cabinet Steel Frame Production Guidelines



13	footboard	1
12	U-steel D	2
11	U-steel C	2
10	U-steel B	2
9	U-steel A	2
8	Stainless steel grounding module	2
7	Unequal Angle steel G	2
6	Unequal Angle steel F	2
5	Unequal Angle steel	4
4	Unequal Angle steel D	4
3	Unequal Angle steel C	1
2	Unequal Angle steel	2
1	Unequal Angle steel A	2
No	Part Name	qty


Technical Requirements:

1. Solid welding, no virtual welding.
2. After welding, except for welding slag, the outer surface of the parts is polished and smooth.
3. Spray protection according to the requirements of the drawing, all stud end faces and threads need spray protection.
4. No dimensioned tolerance according to GB/T 1804-M processing.
5. The unmarked position tolerance shall be executed in GB/T 1184-K class.
6. With* number is an important size, need to focus on inspection.
7. For other dimensions not specified, refer to the 2D/3D drawing.



IMPORTANT!

1. Battery Cabinet must be installed on a reinforced concrete platform base.
2. The concrete pad shall be able to support the weight of the cabinets and to ensure their stability.
3. When designing and manufacturing the embedded steel plates for the battery cabinet, it is necessary to consider that there must be a reliable connection (reinforcement hook) between the embedded steel plate and the concrete base.
4. Battery Cabinet concrete pad minimum carrying capacity shall be 0.8MPa, it is necessary to consider the influence of actual local environmental factors.
5. When molding the concrete pad, it shall protrude below the ground as minimum of 400 mm.
6. The height of the concrete pad above the ground shall be at least 300 mm.
7. Concrete base surface smoothness shall be $\leq 3\text{mm}$.
8. The upper surface tolerance of the foundation shall be $\pm 5\text{mm}$.
9. The concrete pad shall prevent rainwater accumulation on top of it & drainage measures must be taken in the cable trench to prevent water accumulation in the cable trench.

**Concrete Pad with pre-integrated studs**



Support Contact Information

If you have technical problems concerning SolarEdge products, please contact us:

<https://www.solaredge.com/service/support>

Subject to change without notice.

Copyright © SolarEdge Inc.

All rights reserved. June 2024.